

## pfSense - Bug #6664

### It's impossible to use HE.NET tunnel iface as a parent for OpenVPN instances

07/30/2016 04:58 AM - Dmitry K

<b>Status:</b>	Resolved	<b>Start date:</b>	07/30/2016
<b>Priority:</b>	Normal	<b>Due date:</b>	
<b>Assignee:</b>	Jim Pingle	<b>% Done:</b>	0%
<b>Category:</b>	OpenVPN	<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>	2.4.0	<b>Affected Architecture:</b>	All
<b>Affected Version:</b>	All		

**Description**

Setup:

- HE.NET tunnel iface [for example, WAN\_HE]

Steps to reproduce:

- Create an IPv6 OpenVPN instance on parent iface WAN\_HE [for example, OVPN\_AMS]
- Go to dashboard. OVPN\_AMS is down.

Expected:

- OVPN\_AMS is up

Actual:

- "Status -> System Logs -> OpenVPN" has a string "Options error: --local and --nobind don't make sense when used together"

Workaround:

- Edit /var/etc/openvpn/client?.ovpn file by removing **nobind** option
- Restart openvpn service

#### History

##### #1 - 07/30/2016 05:16 AM - Dmitry K

Yet another workaround: Specify a local port instead of empty/0. Looks like **\$iface\_ip** is not properly initialized when he.net iface is chosen.

##### #2 - 09/23/2016 10:18 AM - Jim Pingle

- Target version changed from 2.3.2-p1 to 2.4.0

##### #3 - 01/26/2017 12:13 PM - Jim Pingle

- Status changed from New to Resolved

- Assignee set to Jim Pingle

Between [#6663](#) and [b42ccf1504eca5e40bfb49b0afb688ffe293a7a](#) this is fixed.