

pfSense - Bug #7561

I2tp turn off local user database

05/20/2017 09:19 AM - Jeremy C. Reed

Status:	Resolved	Start date:	05/20/2017
Priority:	Normal	Due date:	
Assignee:	Jim Pingle	% Done:	100%
Category:	L2TP	Estimated time:	0.00 hour
Target version:	2.4.0	Affected Architecture:	All
Affected Version:	All		

Description

vpn_l2tp.php says when RADIUS is set "The local user database will not be used."

and vpn_l2tp_users.php also shows:
"RADIUS is enabled. The local user database will not be used."

I don't see any configuration to turn "internal" off (like "set auth disable internal").

It is not clear if this is about what type of users like L2TP mdp.secrets or what?

But if it is about mdp.secrets then that is used after RADIUS and is enabled by default.

(see <http://mpd.sourceforge.net/doc/mpd31.html#31>)

(I noticed this while working on my book.
My list of bugs is at <http://reedmedia.net/books/pfsense/bugs.html>)

Associated revisions

Revision 5de4b046 - 05/22/2017 10:50 AM - Jim Pingle

Disable internal L2TP users when activating RADIUS, to follow the behavior stated in the GUI. Fixes #7561

History

#1 - 05/22/2017 10:49 AM - Jim Pingle

- Category changed from VPN (Multiple Types) to L2TP
- Status changed from New to Assigned
- Assignee set to Jim Pingle
- Target version set to 2.4.0
- Affected Version set to All
- Affected Architecture All added
- Affected Architecture deleted ()

#2 - 05/22/2017 11:10 AM - Jim Pingle

- Status changed from Assigned to Feedback
- % Done changed from 0 to 100

Applied in changeset [5de4b0463871c9077850ab81ea506d5d5a892439](https://code.djangoproject.com/changeset/5de4b0463871c9077850ab81ea506d5d5a892439).

#3 - 06/15/2017 09:34 AM - Jim Pingle

- Status changed from Feedback to Resolved