

pfSense - Bug #7567

unused openvpn address pool setting?

05/20/2017 09:51 AM - Jeremy C. Reed

Status:	Resolved	Start date:	05/20/2017
Priority:	Normal	Due date:	
Assignee:	Jim Pingle	% Done:	100%
Category:	OpenVPN	Estimated time:	0.00 hour
Target version:	2.4.0	Affected Architecture:	All
Affected Version:	All		

Description

vpn_openvpn_server.php
Address Pool
sets pool_enable.
I don't see any code that uses it, like not in /etc/inc/openvpn.inc
What uses this code?

Also this is for addrpool in the wizard. What uses it?

(I noticed this while working on my book.
My list of bugs is at <http://reedmedia.net/books/pfsense/bugs.html>)

Associated revisions

Revision bc3669e4 - 05/22/2017 11:24 AM - Jim Pingle

Remove references to unused "Address Pool" setting. The address behavior is now determined by the mode, and has been for years. Fixes #7567

History

#1 - 05/22/2017 11:20 AM - Jim Pingle

- Category changed from VPN to OpenVPN
- Status changed from New to Assigned
- Assignee set to Jim Pingle
- Target version set to 2.4.0
- Affected Version set to All
- Affected Architecture set to All

The setting isn't required, the backend behavior is determined by the mode now. Safe to remove.

#2 - 05/22/2017 11:30 AM - Jim Pingle

- Status changed from Assigned to Feedback
- % Done changed from 0 to 100

Applied in changeset [bc3669e4e88cb75eb987ee073a5360f4a69b10b1](https://code.djangoproject.com/changeset/bc3669e4e88cb75eb987ee073a5360f4a69b10b1).

#3 - 06/15/2017 09:35 AM - Jim Pingle

- Status changed from Feedback to Resolved